

Šroubovací otočný bod



| Kód výrobku | Nosnost 0° (t) | Nosnost 90° (t) | Hmotnost (kg) | Utahovací moment (Nm) | Závit | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) |
|-------------|----------------|-----------------|---------------|-----------------------|--------|--------|--------|--------|--------|--------|
| 40305008 | 0,8 | 0,3 | 0,1 | 6–10 | M8×12 | 38 | 26 | 46 | 25 | 8 |
| 40305010 | 1 | 0,4 | 0,1 | 6–10 | M10×14 | 38 | 26 | 46 | 25 | 8 |
| 40305020 | 2 | 0,75 | 0,2 | 10–15 | M12×17 | 44 | 32 | 54 | 33 | 10 |
| 40305040 | 4 | 1,5 | 0,4 | 20–30 | M16×24 | 52 | 38 | 64 | 36 | 14 |
| 40305060 | 6 | 2,3 | 0,7 | 50–70 | M20×30 | 63 | 45 | 79 | 48 | 21 |
| 40305080 | 8 | 3,2 | 1,1 | 120–150 | M24×35 | 74 | 52 | 92 | 53 | 21 |
| 40305120 | 12 | 4,5 | 2,1 | 200–250 | M30×45 | 92 | 65 | 118 | 68 | 24 |
| 40305160 | 16 | 7 | 4 | 280–400 | M36×57 | 105 | 76 | 136 | 82 | 30 |